



rH ₂ :	0...42 rH ₂
pH:	-2...+16 pH
mV:	±2000 mV
Conductivity:	0...2000 mS/cm
Resistivity:	0...200 MΩ.cm
Salinity:	0.0...70.0
TDS:	0...100 g/l
µW:	0...400000 µW
Temperature:	-5...+105°C

Three independent channels for all measurements!

(conductivity: only 2 channels)

rH₂
Bio-electronic multimeter for the study of the biological water quality or illnesses in body fluids according to Vincent's method.

pH
Multi-point (1...5) calibration for more linearity.
Selectable resolution from 0.001 pH to 0.1 pH.
Automatic calibration with any of eleven pre-programmed and five user specified pH buffers. *Create your own buffer/temperature tables!*
Accepts pH electrodes with any zero point (E₀) between ±999 mV.

mV
Features mV calibration for accurate ORP measurements.
Selectable resolution from 0.1 mV to 1 mV.
Can also show mV referred to the standard hydrogen electrode.

Conductivity
Multi-point (1...3) calibration for more linearity.
An electrode with a typical cell constant of 1 cm⁻¹ (standard) permits to measure from 0.01 µS/cm to 200 mS/cm in five ranges.
An electrode with a typical cell constant of 0.1 cm⁻¹ permits to measure from 0.001 µS/cm to 20 mS/cm in five ranges.
An electrode with a typical cell constant of 10 cm⁻¹ permits to measure from 0.1 µS/cm to 2000 mS/cm in five ranges.
Automatically selects correct range and frequency.
Selectable reference temperature: 20° or 25°C.
Automatic calibration with any of three preprogrammed and three user specified standard solutions. *Create your own standard/temperature tables!*
Accurate low conductivity measurements by eliminating the capacitive component of the electrode and its cable (avoid the use of long cables!).

µW
Calculates the resistance (Ω) and the quantification of Vincent (µW).

Temperature
Manual or automatic temperature compensation.
Calibrates temperature probe for quality measurements.

CODE	DESCRIPTION
C3050	Bio-electronic meter (USB version) + USB cable
C3051	Bio-electronic meter (Ethernet version) + UTP cable
C3050T	Meter kit complete: meter + pH/ORP electrode SP35B + conductivity electrode SK20T + 2x50 ml buffers (pH 4 and 7) + 50 ml conductivity standard (0.01 M KCl) + 50 ml electrolyte (3M KCl) + 50 ml redox standard (358 mV) + flexible electrode holder SH300
A4800	Wall mounting kit (optional)
A4049	Car adaptor, 12 V (optional)
➔ Supplied with a mains adaptor (100...240 VAC, EU/US)	
<i>(Add a UK-sign for UK plug versions, e.g.: C3050-UK) (Add a CH-sign for Swiss plug versions, e.g.: C3050-CH)</i>	

Inputs

Two inputs for pH, mV or conductivity + corresponding temperature and reference inputs.

One extra input for pH or mV + corresponding temperature and reference input.

Outputs

Two versions available:

C3050: with USB communication port and RS232 interface.

C3051: with Ethernet communication port and RS232 interface.

Data-logging

Up to 12000 data sets can be stored manually or at a programmable interval.

Allows to mix data from all ranges in the same table.

Download **free data acquisition software** from www.consort.be to view, store and edit the measurements in your computer.

Cabinet

Robust dust and splash-proof cabinet.

An optional wall mounting kit allows to fix the meter to any wall making more space available on the desk.

Display

A large bright LCD screen with white backlight enables to view all channels individually or simultaneously.

Stability indicator prompts the user when readings should be taken.

Hold function allows to freeze the display for convenient reading or recording.

The interactive LCD screen provides step by step instructions in the language of your choice (English, Dutch, French, German).

Real-time clock displays time and date.

Shows a GLP report on the LCD screen.

Special features

Two-way communication with a computer using USB or RS232.

Can be programmed to continue automatically with the measurements or data-logging after a power failure.

Password protection prevents any unauthorised modification of the instrument's settings.

No electrical interference between pH/ORP and conductivity electrodes in the same solution.

Optional 12 V car adaptor.

Three year warranty.

GLP

All procedures for a "Good Laboratory Practice" are on board.

Pre-programmed standards

pH buffers: 1.68, 2.00, 4.00, 4.01, 6.87, 7.00, 9.18, 9.21, 10.01, 12.00, 12.45 (at 25 °C).

Conductivity: 1413 µS/cm, 12.88 mS/cm, 111.8 mS/cm (at 25 °C).

SPECIFICATIONS		C3050 - C3051
pH	Range	-2...+16 pH
	Resolution	0.001 pH
	Accuracy	0.1% ± 1 digit
	Calibration	1...5 points
	Buffers	11 pre-programmed 5 user specified
	Temperature compensation	-5...+105 °C
	ISO-pH	6...8 pH
	Slope	80...120%
	Zero point (Eo)	±999 mV
mV	Range	±2000 mV
	Resolution	0.1 mV
	Accuracy	0.1% ± 1 digit
	Calibration	1 point
rH ₂	Range	0...42 rH ₂
	Resolution	0.01 rH ₂
	Accuracy	0.1% ± 1 digit
CONDUCTIVITY	Range (cc dependent)	0...2000 mS/cm
	Resolution (cc dependent)	0.001 µS/cm
	Accuracy	0.5% f.s. of range
	Calibration	1...3 points
	Standards	3 pre-programmed 3 user specified
	Cell constant (cc)	0.07...13 cm ⁻¹
	Temperature compensation	-5...+105 °C
	Reference temperature	20° or 25 °C
	Temperature coefficient	natural waters (EN27888)
	Range lock	✓
Capacitive compensation	✓	
RESISTIVITY	Range	0...200 MΩ.cm
	Resolution	1 Ω.cm
SALINITY	Range	0...70
	Reference temperature	15 °C
TDS	Range	0...100 g/l
	Resolution	0.01 mg/l
µW	Range	0...400000 µW
TEMPERATURE	Range	-5...+105 °C
	Resolution	0.1 °C
	Accuracy	0.1 °C
	Calibration	1 point
CHANNELS	Measurement	3 (conductivity: 2)
	Temperature	3
INPUTS	Measurement	3 BNC, 10 ¹² Ω
	Temperature	3x2 banana, for Pt1000
CALIBRATION	Reminder	0...999 h
	GLP	✓
DISPLAY	LCD	240x64 pixels
	White backlight	✓
	Hold function	✓
	Selectable resolution	✓
	Real time clock	✓
COMMUNICATION	Interface with computer	USB
	RS232, baud rate	1200...115200 b/s
	Printer	✓
DATA-LOGGING	Data sets	12000 + °C/date/time
	Modes	all
	Manual or timed	✓
	Interval	1...9999 s
SECURITY	Identification number	✓
	Password protection	✓
AMBIENT CONDITIONS	Temperature	0...40 °C
	Humidity	0...95%, non condensing
POWER SUPPLY	Mains	100...240 VAC, 50/60 Hz
	Low voltage	9...15 VDC
DIMENSIONS	WxDxH	26x18x9 cm
WEIGHT	Meter	1 kg

Electrodes supplied with kit versions



SP35B

- pH + ORP
- Glass body, 1 m cable
- 0...14 pH, 0...±2000 mV
- Single junction, refillable



SK20T

- Conductivity + ATC
- Glass body, 1 m cable
- 1 cm⁻¹, 0...110 °C
- Dual graphite plates

rH₂

The rH₂ is a measurement for the level of electronic exchanges between water and dissolved ions. It enables to study incomplete, indeterminate and very diluted aqueous redox solutions.